



# SUBARU LES PLÉIADES 10W-50

Engine oil

*Fully synthetic and very high performance lubricant based on TOTAL technology. Special made for SUBARU Boxer Engines, approved as SUBARU Genuine oil.*

## KEY DATA

### LIGHT VEHICLE RANGE

**PETROL ENGINE OIL for SUBARU Boxer Engines**

**SAE : 10W50**

**SYNTHETIC TECHNOLOGY**

### INTERNETIONAL STANDARDS

✓ API : SM/CF

### MANUFACTURER CERTIFICATIONS

✓ SUBARU

✓ Applicable engine types

EJ20, EJ25, EG33, EZ30 and EZ36,  
(both naturally aspirated and turbocharged boxer engines)

✓ Not applicable for FA and FB engines.

## Applications

**Suitable for SUBARU boxer engines**

**Adapt in the severe conditions**

**Fit for high boost turbocharged engines**

- Can be used for EJ and EZ types of SUBARU boxer engines including turbocharged
- Perfectly adapt sport and race track type driving under the most difficult operating conditions
- Appropriate for IMPREZA WRX and other high output performance tuned boxer engines with the most stringent requirements

## Customer Benefit

**Anti-wear protection**

**Thermal stability**

**Engine cleanliness**

**Extended engine life**

- Maintains the most resistant oil films even at very high temperature
- Provides an exceptional anti-wear protection for the engine, especially in the most severe conditions
- Outstanding thermal stability and oxidation resistance preventing degradation in the most severe conditions
- Keeps the engine clean and develops performance and power
- Lubricates engine parts immediately during cold starts, resulting in extended engine life

## Characteristics

Test	Unit	Test method	Result
Viscosity grade	-	SAE J300	10W-50
Kinematic viscosity at 40°C	mm <sup>2</sup> /s	ASTM D445	119.4
Kinematic viscosity at 100°C	mm <sup>2</sup> /s	ASTM D445	17.50
Viscosity index	-	ASTM D2270	162
Viscosity HTHS 150°C	mPa.s	CEC L 36 A-90	4.5
Pour Point	°C	JIS K2269	-33
Flash Point	°C	ASTM D92	230
B.N	mgKOH/g	ASTM D2896	10.6

\*The characteristics given above are obtained with a standard tolerance threshold during production and may not be considered specifications.

## Recommendations

Before using the product, the vehicles maintenance guide should be checked. Oil changes should be carried out in accordance with the manufactures recommendations.

The product should not be stored at temperatures over 60 °C. It should be kept away from sunlight, intense cold and extreme temperature fluctuations.

If possible, the package should not be exposed to elements. Otherwise, the drums should be laid horizontally in order to avoid any contamination from water and to prevent the products label from rubbing off.

## Health, safety and the environment

Based on the toxicological information available, this product should not cause any adverse health effects, provided it is used for its intended purpose and in accordance with the recommendations laid out in the Safety Data Sheet. This can be obtained on request from your reseller and is available for consultation at [www.quickfds.fr](http://www.quickfds.fr)

This product should not be used for any purpose other than the ones for which it is intended.

When disposing of this product after use, please protect the environment and comply with local regulations.